



Application Industry: Paper-making White Water Wet End Effluent treatment PCB Cleaning

Product Name: Antifoam RK-300P

RK-300P is a modified polyether silicone compound emulsion defoamer. It has good dispersibility in the foaming system. No silicone grease precipitation and flotation.

Product property:

Good defoaming & antifoaming performance at lower concentration

Defoaming in mid-low temperature water system, strong versatility

Good dispersion in water

Excellent performance in papermaking white water above 60°C.

Main physical and chemical properties:

Item	Range
Appearance	Milky-white liquid
Viscosity	100~300mPa·s
Solid content	30±1%
pH value	6.5-8.5

Key Applications

Papermaking white water above 60 °C

Industrial waste water treatment

PCB cleaning

Textile printing , starch gelatinization in normal temperature

LIMITATIONS

This product is neither tested nor represented as suitable for medical or pharmaceutical uses

Information of manufacturers and products

Product name	Antifoam
Model	RK-300P
Manufacturer	Xiamen Rickman Chemical Technology CO., Ltd. Add: No 1267Qianpu South Road, Siming District, Xiamen City, Fujian Province, China



Tel/Fax	15359255189
---------	-------------

Product content

Pure or mixture	Mixture
English name	Silicone-polyether

Dangerous marks

Human-body health effect	Skin contact	Slightly skin allergic for variety of people
	Eye contact	Eye allergic
	Swallow	No data
Environment effect	No data	
Physical/chemical damage	——	
Special damage	——	

Packaging & Storage

Package	25kg/ 50kg/200kg plastic pail or 1000kg IBC
Storage Condition	Room Temperature Storage (5°C-40°C) , avoid direct sun light, shelf life is 6 months.

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of Rickman products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end application.