



Application Industry: Oil-based Ink Coating Resin

Product Name: Antifoam RK-2200

RK-2200 is a general and special modified non-silicon defoamer, especially suitable for polyurethane, epoxy floor paint, solvent-free UV curing, polyester system, etc. It has excellent defoaming and antifoaming performance, balanced dispersibility and extremely high compatibility, and will not precipitate in the system and form shrinkage holes.

Product property:

- Especially effective for microbubbles
- Good performance in high viscosity systems
- Stable system compatibility
- Excellent anti-foaming effect in different oil systems

Main physical and chemical properties:

Item	Range
Appearance	Colorless to light yellow transparent liquid
Active content	100%

Application Process:

It can be added directly, and the amount of defoamer added can be 0.2%~0.6%. The best amount of addition is determined by the customer based on the specific requirements of the application site and the actual situation. If dilution is required, it can also be diluted with a special diluent before use.

Key Applications

- Oil-based polyurethane, epoxy, polyester, adhesive system
- Oil-based ink, water-based ink, coating, resin system
- Solvent-free UV curing system

LIMITATIONS

This product is neither tested nor represented as suitable for medical or pharmaceutical uses

Information of manufacturers and products

Product name	Antifoam
Model	RK-2200
Manufacturer	Xiamen Rickman Chemical Technology CO., Ltd. Add: No 1267 Qianpu South Road, Siming District, Xiamen City,



	Fujian Province, China
Tel/Fax	15359255189

Product content

Pure or mixture	Mixture
English name	Special non-silicon

Dangerous marks

Human-body health effect	Skin contact	Slightly skin allergic for variety of people
	Eye contact	Eye allergic
	Swallow	No data
Environment effect	No data	
Physical/chemical damage	——	
Special damage	——	

Packaging & Storage

Package	25kg/ 50kg/120kg/ 200kg plastic pail or 1000kg IBC
Storage Condition	Room Temperature Storage (5°C-40°C) , Avoid direct sun light, shelf life is 12 months.

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained here is offered in good faith and is believed to be accurate. However, because conditions and methods of use of Rickman products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end application.