



Application Industry: Emulsion Adhesives Latex Paints Pressure-Sensitive Adhesives

Product Name: Antifoam RK-980P

RK-980P is a 100% active content mineral oil antifoam. It's very high efficiency, great persistence and compatibility, which is suitable for acrylic acid, vinyl acetate, acetic acid, styrene-acrylic, copolymer emulsion, coating, resin, detergent, sewage treatment.

Product property:

Good compatibility and long foam control time

Excellent dynamic defoaming performance

Main physical and chemical properties:

Item	Range
Appearance	Light offwhite or light yellow liquid
Viscosity(25°C)	100~1500mPa·s
Active content	100%

Application Process:

Can be added directly during production, or use after pre-dispersing

The additive amount is 0.1-0.6% of general weight, which can effectively extinguish or prevent foam regeneration.

Key Applications

Emulsion adhesives, all kinds of latex paints, pressure-sensitive adhesives

Water borne paints and inks

Acrylic acid, vinyl acetate, acrylic acid, styrene-acrylic acid, copolymer and other emulsified coatings

Latex

LIMITATIONS

This product is neither tested nor represented as suitable for medical or pharmaceutical uses



Information of manufacturers and products

Product name	Antifoam
Model	RK-980P
Manufacturer	Xiamen Rickman Chemical Technology CO., Ltd. Add: No 1267 Qianou South Road, Siming District, Xiamen City, Fujian Province, China
Tel/Fax	15359255189

Product content

Pure or mixture	Mixture
English name	Mineral oil

Dangerous marks

Human-body health effect	Skin contact	Slightly skin allergic for variety of people
	Eye contact	Eye allergic
	Swallow	No data
Environment effect	No data	
Physical/chemical damage	——	
Special damage	——	

Packaging & Storage

Package	25kg/ 50kg180kg plastic pail or 850kg IBC
Storage Condition	Room Temperature Storage (5°C-40°C) , Avoid direct sun light, shelf life is 12 months.

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained here is offered in good faith and is believed to be accurate. However, because conditions and methods of use of Rickman products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end application.